


MAFR300L series

AIR UNITS (F.R.UNIT)



Symbol:



- Longer case for adapting high efficient auto drain valve.

Specification:

Model	MAFR300L	
Bore No.	8A	10A
Port size	Rc(PT) 1/4	Rc(PT) 3/8
Medium	Air	
Operating pressure range	0~9.9 kgf/cm ² (0~0.99 MPa)	
Proof pressure	15 kgf/cm ² (1.5 MPa)	
Effective orifice	32 mm ²	34 mm ²
Regulated pressure range	0.5~8.5 kgf/cm ² (0.05~0.85 MPa)	
Ambient temperature	-5~+60°C (No freezing)	
Filter element	Standard: 5 μm Option: 40 μm	
Attachment	Pressure gauge (PG-40), bracket	
Weight	452 g	

※ Standard unit contains semi-auto-drain function when operating pressure below 0.5 kgf/cm².

Order example:

MAFR300L — 8A — □ — □ — BSP

MODEL

BORE SIZE

8A: PT 1/4
10A: PT 3/8

D: auto drain valve
(MADV 300)

FILTER
ELEMENT
Blank: 5 μm
40u: 40 μm

PORT THREAD

Blank: PT thread
BSP: BSP thread
NPT: NPT thread

Flow feature:

