

AltaBlue™ Touch Series Standard Format Adhesive Melters

15, 30 and 50 liter Melters

Nordson® AltaBlue touch series melters are designed for precise, demanding hot melt adhesive applications. A choice of metering spur-gear pumps with variable-speed AC motors and key-to-line functionality satisfies a wide range of manufacturing requirements. A non-stick coated tank and reservoir design reduces adhesive degradation while maximizing adhesive throughput. The Optix™ user interface offers a color LCD touch screen for intuitive control.

AltaBlue touch series melters enable pressure and flow monitoring and control through optional control boards. This integrated solution simplifies the system and reduces cost while providing a means for measuring and controlling material dispense rate in response to production rate changes. Through variation management, material consumption is reduced while product quality and production efficiency are enhanced.

AltaBlue touch series melters:

- Offer intuitive control via Optix user interface
- Enable pressure and flow monitoring and control through an integrated option
- Provide reliable day-to-day operation
- Simplify routine maintenance
- Maximize production up-time
- Serve a broad range of industries



Specifications

Type of System	Release-coated tank and reservoir Spur-gear pump with variable-speed AC motor
Number of Pumps	Up to 2 single or dual stream pumps
Maximum Pump Rate^{1 & 2}	1.4 to 82.1 kg/hr (3 to 181 lb/hr)
Number of External Heating Channels	Configurable up to 6 pairs
Filter Type	Basket-style, inside-out filter
Maximum Working Hydraulic Pressure	85 bar/8.5 MPa (1230 psi)
Operating Temperature Range	40 to 230°C (100 to 450°F)
Ambient Temperature Range	0° to 50°C (32 to 122°F)
Temperature Control Stability	±1°C (2°F)
Maximum External Power Capacity	
Channel 1, 2, 5, 6 (each)	1,200 watts per pair/1,000 watts per channel
Channel 3, 4 (each)	2,000 watts per pair/2,000 watts per channel
Electrical Service³	200 to 240 VAC 3 phase 50/60 Hz 380 to 415 VAC-Y (3 phase N/PE) 50/60 Hz 400 VAC 3 phase 50/60 Hz ⁴ 480 VAC 3 phase 50/60 Hz ⁴
Input/Output Capability Standard	3 STD outputs - programmable for function 4 STD inputs - programmable for function
Temperature Control Sensor Options	Nickel 120 Ohm RTD, Platinum 100 Ohm RTD
Ingress Protection Standard	IP33
Melter Dimensions (W x H x D)	525 x 1465 x 950 mm (20.7 x 57.7 x 37.4 in.)
Installation Dimensions (W x H x D)	2355 x 1465 x 2780 mm (92.7 x 57.7 x 109.5 in.)

	AltaBlue 15	AltaBlue 30	AltaBlue 50
Holding Capacity	15 L (915 in ³) 14.5 kg (32 lb)	30 L (1831 in ³) 29 kg (64 lb)	50 L (3051 in ³) 47.5 kg (104.7 lb)
Throughput (per hour) ¹	28 kg (62 lb)	45 kg (99 lb)	50 kg (110 lb)
Melt Rate (per hour) ¹	15 kg (33 lb)	30 kg (66 lb)	50 kg (110 lb)
Weight (empty) ⁶	200 kg (440 lb)	225 kg (500 lb)	250 kg (550 lb)
Maximum System Power Capacity	15,037 watts	16,237 watts	19,437 watts

Configurable options available include:

- Pressure and flow monitoring and control (motor driven)
- Manual and pneumatic flow control
- Remote visual system (warning light tower system)
- Low level indication
- Communication: Ethernet, DeviceNet™, Profibus®
- Expanded I/O
- Motion switch

¹ Actual rates will vary depending on adhesive type, application parameters and input voltage.

² Range given is for maximum pump rate of various pumps available.

³ Permitted deviation from rated line voltage is ±10%.

⁴ With integrated transformer.

⁵ Weight depends on melter configuration.

Profibus is a trademark of Profibus International.

DeviceNet is a trademark of Open DeviceNet Vendor Association, Inc.

Nordson and the Nordson logo/design are trademarks of Nordson Corporation.

For more information, speak with your Nordson representative or contact your Nordson regional office.

United States

Duluth, Georgia
(800) 683-2314 **Phone**
(866) 667-3329 **Fax**

Canada

Markham, Ontario
(800) 463-3200 **Phone**
(905) 475-8821 **Fax**

Europe

Erkrath, Germany
(49) 211-9205-0 **Phone**
(49) 211-254658 **Fax**

Japan

Tokyo, Japan
(81) 3-5762-2700 **Phone**
(81) 3-5762-2701 **Fax**

Asia/Australia/ Latin America

Amherst, Ohio
(440) 985-4797 **Phone**
(440) 985-1096 **Fax**

Find us on:



*Learn more about
AltaBlue touch melters*