


MACP400 series

AIR UNITS (F.R.L.UNIT)



Symbol:



Order example:

MACP400 – 10A – □ – □ – BSP

MODEL

BORE SIZE




8A: PT 1/4
10A: PT 3/8
15A: PT 1/2

FILTER

ELEMENT
Blank: 40 μ m
5u: 5 μ m

D: auto drain valve
(FMRF 300)

PORT THREAD
Blank: PT thread
BSP: BSP thread
NPT: NPT thread



Specification:

Model	MACP400		
Components	MAFR400, MAL400		
Bore No.	8A	10A	15A
Port size	PT 1/4	PT 3/8	PT 1/2
Medium	Air		
Operating pressure range	0~9.9 kgf/cm ² (0~0.99 MPa)		
Proof pressure	15 kgf/cm ² (1.5 MPa)		
Regulated pressure range	0.5~8.5 kgf/cm ² (0.05~0.85 MPa)		
Ambient temperature	-5~+60°C (No freezing)		
Filter element	Standard: 40 μ m Option: 5 μ m		
Lubricating oil capacity	200c.c		
Min. flow for oil drip	50 ℓ /min	200 ℓ /min	400 ℓ /min
Recommended lubricating oil	Turbine oil ISO-VG32		
Attachment	Pressure gauge(PG-50), bracket		
Weight	2300 g		

Flow feature:

