



Features

Be widely used in vacuum systems. Efficiently protect the pump from the product entering it. Also protect the system components (valves, gauges)

Consist of a steel housing and a lid with quick locking clips. Rugged all steel construction for heavy duty applications. Quickly exchangeable cartridge. Large dirt holding capacity and easy cleaning. High separation efficiency: 99% removal for 5 micron, Brazed fittings for high vacuum duty (F002–F006) Low pressure drop

Technical Parameters

Model	BF002	BF002-1	BF004	BF003	BF006
Rated flow rate m ³ /h	32	42	100	120	300
*A(Inch)	G1/2"	G3/4"	G1 1/4"	G1 1/4"	G2"
*B(Inch)	G1/2"	G3/4"	G1 1/4"	G1 1/4"	G2"
C	Φ 101	Φ 101	Φ 146	Φ 185	Φ 222
D	90	90	110	170	258
E	53	53	70	115	125
F	70	70	75	130	240
Weight	1	1	1.4	2.3	6.9
Dimension A,B is pipe thread, G.America is NP, Britain is BSP					
Filtration consumables	FE002	FE002	FE004	FE003	FE006
O.D	Φ 65	Φ 65	Φ 98	Φ 128	Φ 150
I.D	Φ 38	Φ 38	Φ 60	Φ 64	Φ 88
Height	69	69	70	125	222

Dimensions(mm)

