


# MAR200 series

AIR UNITS (R. UNIT)



Symbol:



## Specification:

| Model                    | MAR200                                                     |        |
|--------------------------|------------------------------------------------------------|--------|
| Bore No.                 | 6A                                                         | 8A     |
| Port size                | PT 1/8                                                     | PT 1/4 |
| Medium                   | Air                                                        |        |
| Operating pressure range | 0~9.9 kgf/cm <sup>2</sup> (0~0.99 MPa)                     |        |
| Proof pressure           | 15 kgf/cm <sup>2</sup> (1.5MPa)                            |        |
| Regulated pressure range | Standard type: 0.5~8.5 kgf/cm <sup>2</sup> (0.05~0.85 MPa) |        |
| Ambient temperature      | -5~+60°C (No freezing)                                     |        |
| Attachment               | Bracket                                                    |        |
| Option                   | Pressure gauge (PG-40)                                     |        |
| Weight                   | 190 g                                                      |        |

## Order example:

**MAR200 — 6A — 1K — C — BSP**

MODEL

BORE SIZE  
6A: PT 1/8  
8A: PT 1/4

Adjustable Press. Range  
Blank: Standard Type  
1K: 0~1 kgf/cm<sup>2</sup>  
2K: 0~2 kgf/cm<sup>2</sup>  
3K: 0~3 kgf/cm<sup>2</sup>  
4K: 0~4 kgf/cm<sup>2</sup>

PRESSURE  
GAUGE  
(PG-40)

PORT THREAD  
Blank: PT thread  
BSP: BSP thread  
NPT: NPT thread

## Flow feature:

